## **Phos-Chek Fortify – Pretreatment**

Phos-Chek Fortify is a pretreatment formulation that uses ammonium phosphate salts as the fire-retardant active ingredient. Fortify contains a thickener to provide a low viscosity product, this product category is qualified to be purchased and delivered premixed; the liquid concentrate is not evaluated for long-term stability.

Product Type:	Low viscosity, gum-thickened, pretreatment, pre-mixed retardant.
Application:	Ground-based fire apparatus.
Use level:	These products are pre-mixed and delivered ready-to-use.
Yield:	Not applicable.
Viscosity:	150 – 400 centipoise (cP)
	Field measurement (Marsh Funnel): A flow-through time of 32 – 40 seconds using the Low Viscosity Marsh Funnel with 3/16 inch tip indicates an acceptable viscosity.
Salt content:	Field measurement (refractometer): A reading of 11.0 indicates proper salt content. A reading between 10.0 and 12.0 indicates an acceptable salt content.
Specific weight:	8.86 lb/gal for mixed retardant; equivalent to a density of 1.062 g/mL. At 70°F, a density between 1.054 and 1.070 indicates an acceptable salt content. This is equivalent to 8.80 lb/gal – 8.93 lb/gal.
	The mixed product and liquid concentrate are non-storable.