

Material Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: PHOS-CHEK® FIRE RETARDANT GRADES D-75F AND D-75R

Reference Number: AST10035 Date: March 27, 2003

Company Information:

Worldwide Headquarters Europe Headquarters ASTARIS LLC ASTARIS S.r.I.

622 Emerson Road - Suite 500 Via Brescia 26

St. Louis, Missouri 63141 20063 Cernusco sul Naviglio MI

Italy

Emergency telephone: In Europe call +32 (0) 3 568 5123

In USA call CHEMTREC: 1 800 424 9300 In Canada call CANUTEC: 1 613 996 6666

General Information: +32 (0) 2 921 02442 (Europe)

+1 800 424 6166 (Worldwide)

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Component</u>	CAS No.	% by weight	
Diammonium Sulfate	7783-20-2	> 65	
Monoammonium Phosphate	7722-76-1	> 15	
Diammonium Phosphate	7783-28-0	> 5	
Guar Gum, Hydroxypropyl	39421-75-5	<10	
Performance Additives +	Trade Secret	<5	

+ Components are Company Trade Secret - Business Confidential. Astaris is withholding the specific chemical identity under provision of the OSHA Hazard Communication Rule Trade Secrets (1910.1200(i)(1)). The specific chemical identity will be made available to health professionals in accordance with 29 CFR 1910.1200 (i)(1) (2) (3) (4)...

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Appearance and Odor: Reddish colored mixture of powdered and granular components with little or no odor.

WARNING STATEMENTS

WARNING!

CONTAINS GUAR GUM WHICH CAN CAUSE ALLERGIC RESPIRATORY REACTION MAY CAUSE RESPIRATORY TRACT IRRITATION

POTENTIAL HEALTH EFFECTS

Material: Phos-Chek® Fire Retardant Grades D-75F and D-75R

Page 2 of 6 Reference No.: AST10035 February 11, 2003

Likely Routes of Exposure: Skin contact and dust inhalation

EYE CONTACT: No more than slightly irritating based on toxicity studies. The dry powder may cause foreign body irritation in some individuals.

SKIN CONTACT: No more than slightly toxic based on toxicity studies. Non irritating based on toxicity studies. The dry powder may cause drying or chapping of the skin.

INHALATION: May cause nasal and respiratory tract irritation based on toxicity information of components. May cause an allergic respiratory tract reaction based on toxicity information of quar gum.

INGESTION: Not toxic if swallowed based on toxicity studies. No significant adverse health effects are expected to develop if only small amounts (less than a mouthful) are swallowed.

Refer to Section 11 for toxicological information.

4. FIRST AID MEASURES

IF IN EYES OR ON SKIN, immediate first aid is not likely to be required. However, this material can be removed with water. Remove material from eyes, skin and clothing. Wash heavily contaminated clothing before reuse.

IF INHALED, remove to fresh air. If breathing, immediate first aid is not likely to be required. If breathing is difficult, give oxygen. If not breathing give artificial respiration. Get medical attention.

IF SWALLOWED, immediate first aid is not likely to be required. A physician or Poison Control Center can be contacted for advice.

5. FIRE FIGHTING MEASURES

FLASH POINT: Not combustible

HAZARDOUS PRODUCTS OF COMBUSTION: Not applicable

EXTINGUISHING MEDIA: Not applicable

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known

FIRE FIGHTING EQUIPMENT: Not applicable

6. ACCIDENTAL RELEASE MEASURES

In case of spill, sweep, scoop or vacuum and remove. Flush residual spill area with water.

Refer to Section 13 for disposal information and Sections 14 and 15 for reportable quantity information.

7. HANDLING AND STORAGE

HANDLING

Material: Phos-Chek® Fire Retardant Grades D-75F and D-75R

Page 3 of 6 Reference No.: AST10035 February 11, 2003

Avoid breathing dust. Keep container closed.

Use with adequate ventilation.

Emptied container retains dust and product residue. Observe all labeled safeguards until container is cleaned, reconditioned, or destroyed. The reuse of this material's container for nonindustrial purposes is prohibited and any reuse must be in consideration of the data provided in the MSDS.

STORAGE: Product is stable under normal conditions of storage and handling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: This product does not cause significant eye irritation or eye toxicity requiring special protection. Use good industrial practice to avoid eye contact.

SKIN PROTECTION: Although this product does not present a significant skin concern, minimize skin contamination by following good industrial practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after handling.

RESPIRATORY PROTECTION: Avoid breathing dust. Use NIOSH/MSHA approved respiratory protection equipment when airborne exposure is excessive. Consult respirator manufacturer to determine appropriate type equipment for given application. Observe respirator use limitations specified by NIOSH/MSHA or the manufacturer. Respiratory protection programs must comply with 29 CFR ' 1910.134.

Attention! Repeated or prolonged inhalation may cause allergic respiratory reaction in some people.

VENTILATION: Provide natural or mechanical ventilation to minimize exposure. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

AIRBORNE EXPOSURE LIMITS:

Product/Component **OSHA PEL** ACGIH TLV

Phos-Chek Fire Retardant Grades D-75F AND D-75R None Established None Established

OSHA and ACGIH have not established specific exposure limits for this material. However, OSHA and ACGIH have established limits for particulates not otherwise classified (PNOC) which are the least stringent exposure limits applicable to dusts.

ACGIH TLV OSHA PEL

15 mg/m3 (total dust) 8-hr TWA 10 mg/m3 (inhalable) 8-hr TWA 5 mg/m3 (respirable) 8-hr TWA 3 mg/m3 (respirable) 8-hr TWA

Components referred to herein may be regulated by specific Canadian provincial legislation. Please refer to exposure limits legislated for the province in which the substance will be used.

9. PHYSICAL AND CHEMICAL PROPERTIES

Reddish powder Appearance: Odor: Essentially odorless

Viscosity: 1000-2000 centipoise @ 21 degrees C (70 degrees F) when dissolved

in water at the recommended level of 1.20 pounds per gallon of water.

PH: 5.5-6.5

Material: Phos-Chek® Fire Retardant Grades D-75F and D-75R Page 4 of 6
Reference No.: AST10035 February 11, 2003

NOTE: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any

specific lot or as specifications for the product.

10. STABILITY AND REACTIVITY

STABILITY: Product is stable under normal conditions of storage and handling.

MATERIALS TO AVOID: None known

HAZARDOUS DECOMPOSITION PRODUCTS: Ammonia and phosphoric acid may be formed when these products are heated above 90 degrees C (194 degrees F). Further decomposition resulting in sulfur dioxide may occur at approximately 250 degrees C (482 degrees F).

HAZARDOUS POLYMERIZATION: Does not occur.

11. TOXICOLOGICAL INFORMATION

Data from laboratory studies conducted by Astaris with PHOS-CHEK Fire Retardant, Grades D-75F and D-75R are summarized below.

	Oral LD50 (Rat)	Dermal LD50 (Rabbit)	Eye Irritation (Rabbit)	Skin Irritation (4-hr, Rabbit)
PHOS-CHEK D-75F	Slightly Toxic Q(>505 mg/kg)	No More Than Slightly Toxic (>2,020 mg/kg)	Slightly Irritating	Nonirritating
PHOS-CHEK D-75F 1.2 lbs/gal Solution	Practically Nontoxic (>5050 mg/kg)	No More Than Slightly Toxic (>2,020 mg/kg)	Practically Nonirritating	Nonirritating
PHOS-CHEK D-75R	Slightly Toxic (>4249 mg/kg)	No More Than Slightly Toxic (>2,020 mg/kg)	Practically Nonirritating	Nonirritating
PHOS-CHEK D-75R 1.2 lbs/gal Solution	Practically Nontoxic (>5,050 mg/kg)	No More Than Slightly Toxic (>2,020 mg/kg)	Practically Nonirritating	Nonirritating

COMPONENTS

Data from Astaris studies and/or the available scientific literature on the components of this material which have been identified as hazardous chemicals under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200) are discussed below:

Diammonium Sulfate

Diammonium sulfate was slightly toxic orally and no more than slightly toxic after skin application (rabbits). It was slightly irritating to rabbit eyes and nonirritating to rabbit skin. Inhalation of diammonium sulfate by guinea pigs was reported to produce lung effects and, at high level exposures, animal deaths due to shock and airway constriction. Repeated inhalation had no effect on lung defense mechanisms of hamsters, but was reported to increase the incidence of

Material: Phos-Chek® Fire Retardant Grades D-75F and D-75R Page 5 of 6

Reference No.: AST10035 February 11, 2003

emphysema in comparison to controls. Aerosols of diammonium sulfate aggravated artificially induced emphysema in rats. Diammonium sulfate produced no genetic changes in standard tests using bacterial cells.

Guar Gum, hydroxypropyl

PHOS-CHEK Fire Retardant, Grades D-75F and D-75R contain hydroxypropylguar, which was reported to be irritating to eyes and respiratory tract. Respiratory allergenic responses were reported following repeated exposures in a study of a small group of exposed workers.

12. ECOLOGICAL INFORMATION

Astaris has not conducted environmental toxicity or biodegradation studies with this product.

The following data have been classified using the criteria adopted by the European Economic Community (EEC) for aquatic organism toxicity.

> 1,000 mg/l 24-hr LC50 Daphnia Magna: **Practically Nontoxic** Practically Nontoxic 48-hr LC50 Rainbow Trout: > 1,000 mg/l 48-hr LC50 Fathead Minnow: > 1,000 mg/l Practically Nontoxic

13. DISPOSAL CONSIDERATIONS

This material when discarded is not a hazardous waste as that term is defined by the Resource, Conservation and Recovery Act (RCRA), 40 CFR 261. Dry material may be landfilled or recycled in accordance with local, state and federal regulations. Consult your attorney or appropriate regulatory officials for information on such disposal.

14. TRANSPORT INFORMATION

The data provided in this section is for information only. Please apply the appropriate regulations to properly classify your shipment for transportation.

US DOT

Not hazardous for transport

Canadian TDG

Not hazardous for transport

15. REGULATORY INFORMATION

TSCA Inventory: All Components Listed

DSL Inventory: Listed

WHMIS Classification: D2(B) - Materials Causing Other Toxic Effects

SARA Hazard Notification

Hazard Categories Under Title III Rules (40 CFR 370): Immediate

Section 302 Extremely Hazardous Substances: Not Applicable
Section 313 Toxic Chemical(s): When put in solution, this product contains aqueous ammonia from dissociable ammonium salts. 2.2 percent of this dry powder product is reportable under the requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

CERCLA Reportable Quantity: Not applicable

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation and the MSDS contains all the information required by the

Material: Phos-Chek® Fire Retardant Grades D-75F and D-75R

Page 6 of 6 Reference No.: AST10035 February 11, 2003

Canadian Controlled Products Regulation.

Refer to Section 11 for OSHA/HPA Hazardous Chemical(s) and Section 13 for RCRA classification.

16. OTHER INFORMATION

	Health	Fire	Reactivity	Additional Information
Suggested NFPA Rating Suggested HMIS Rating	1 1	0	0	E

Reason for revision: New toxicological data Supersedes MSDS dated: June 27, 2000

Product Use: Fire Retardant

Phos-Chek ® is a registered trademark of Astaris LLC. Astaris® is a trademark of Astaris LLC

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, Astaris LLC makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Astaris LLC be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS

AST10035.1000.doc