Thermo Technologies, L.L.C.

Material Safety Data Sheet

May be used to comply with OSHA's Hazard

Communication Standard, 29 CFR 1910.1200.

Standards must be consulted for specific requirements.

Identity (As used on Label and List)

Thermo-Gel® 200L

U.S. Department of Labor

Occupational Safety and Health Administration

(Non-Mandatory Form) Form Approved OMB No. 1218-0072

Note: Blank Spaces are not permitted. If any item is not

applicable, or no information is available, the space must

be marked to indicate that.

Emergency Telephone Number:

Section I (800) 424-9300

Distributor's Name and Address Telephone Number for Information:

(701) 258-8208

Thermo Technologies, L.L.C. Date prepared: NA = Not Applicable3811 Lockport Street 8/06/02 NE = Not Established Bismarck, ND 58503 Signature of Preparer (optional) NH = Non-Hazardous

Section II – Hazardous Ingredients/Identity Information Serial Number 0485-1

Hazardous Components (Specific Chemical Identity; Common Name (s))	OSHA PEL NE	ACGHI TLV NE	Other Limits Recommended Irritant (eye)	% (Optional) 20-30
Polyacrylate Polymer CAS No. 25987-30-8				
Petroleum hydrocarbon CAS No. 6472-55-8	5 mg/m3*	5 mg/m3*	*(Oil mist in air)	20-30
Surfactant CAS No. 9016-45-9	NE	NE	Irritant (eye, skin)	1-5

The final components of this product are listed in the US TSCA Chemical Substance Inventory. This product is not transport regulated.

SARA Section 313 Reportable Toxic Chemicals – NONE%

Section III – Physical/Chemical Characteristic

Boiling Point 96°C Specific gravity (H2O=1) Approx. Initial 1.1 Vapor Pressure (mm Hg.) Not established NE **Melting Point** Not established NE Vapor Density (Air=1) Not established NE **Evaporation Rate** Not established NE (Butyl Acetate =1)

Solubility in Water Emulsifies in water with some soluble components present. Appearance and Odor White opaque liquid with mild odor of hydrocarbon.

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) Greater than 100°C (components summary) Flammable Limit LEL NE UEL NE

Extinguishing Media Water fog, CO2, dry chemical extinguishments.

Special Fire Fighting Procedures Use water fog. Avoid water jet/stream. Use self-contained breathing apparatus

and protective gear for any hostile fire. Spilled product creates slippery

conditions.

Unusual Fire and Explosion Hazards Petroleum hydrocarbon component, although formulated to prevent separation, if

separated can burn. Its flash point is in the range of 265°F (method: Cleveland

Open Cup).

Thermo-Gel® 200L 08/06/02 Serial No. 0485-1

Section V – Reactivity Data

Stability Unstable Conditions to Avoid None known.

X Stable

Incompatibility (Material to Avoid)Strong oxidizers, strong acids.

Hazardous Decomposition or ByproductsOn thermal decomposition, oxides of carbon and nitrogen.

Hazardous May Occur Conditions to Avoid None known.

Polymerization X Will not Occur

Section VI - Health Hazard Data

Routes of Entry Inhalation: Yes Skin: Yes Ingestion: No

Health Hazards(Acute and Chronic)

Components, surfactants will irritate the eyes and skin. Wear safety goggles when handling concentrate. Irritation of the mucous membranes may result from inhalation of vapors/mist

forms.

Carcinogenicity NTP: No IARC: No OSHA: No

Signs and Symptoms of Exposure Reddening, swelling of the affected area with burning, itching or other discomfort.

Medical Conditions Generally Not confirmed. Existing cuts, rashes, allergies and other sensitive areas.

Aggravated by Exposure Respiratory disorder may be aggravated.

Emergency and First Aid Procedures Eyes: flush thoroughly with water. Skin: wash with soap and water.

Inhalation: move to fresh air. Ingestion: If ill effects occur, get medical attention. For any continued discomfort/discoloration get professional medical attention.

<u>Section VII – Precautions for Safe Handling and Use</u>

Steps in Case of Contain. Wear protective gear. Collect, using suitable absorbent if needed. Flush residuals to the drain **Released/Spill** for normal biological wastewater treatment. Put collected material into suitable containers for proper

disposal. Exercise caution in spill area as spilled material creates very slippery conditions.

Waste Disposal Incinerate according to applicable regulations. Diluted liquid form may be control release to normal

Method wastewater treatment upon approval of authorities.

Precautions to be Contains surfactants, handle as eye and skin irritant. Gloves and goggles are recommended when Taken in Handling/ handling the concentrate. Avoid inhalation of vapors/mist forms. Do not ingest.

Storage

Other Precautions Exercise caution with spilled product as very slippery conditions, especially in contact with water,

are created. Prevent release of material to waterways.

<u>Section VII – Control Measures</u>

Respiratory Protection Not required for normal product end use. Observe any Section II MSDS exposure limits.

Ventilation Local Exhaust Ensure vapors/mist forms are removed. Special Not required.

Mechanical Recommended Other Ventilation Not required.

Protective Gloves Impervious neoprene or rubber. **Eye Protection** Safety goggles.

Other Protective Apron, shoes, or other to prevent Clothing or Equipment skin contact. Work/Hygienic Wash thoroughly after handling. Practices